



CUMIN – TESSA

<https://cumin.univ-lille.fr/>



Aging study of a second-life battery in a PV-based charging station

Bibaswan BOSE¹, Ronan GERMAN¹, Eric HITTINGER²

¹ L2EP, Université de Lille, France

² Rochester Institute of Technology, USA



Context and Objective



CUMIN Program (Campus of University with Mobility based on Innovation and carbon Neutrality)


Different projects and disciplines to reduce GHG emissions due to transports



TESSA Project : Techno-Economical Study of Stationary life batteries for Affordable e-mobility campus
Using EV battery for solar-based EV charging station

Technical question

How to predict battery aging?



Economic question

When is the best moment to switch to second life ?



Objective: Estimate the power demand of a stationary battery (Energy Storage System) used in PV-based EV charging station



<https://cumin.univ-lille.fr/>




Modelling, control and EMS of solar-based EV charging station



PV-based charging station model and EMR



Structural Scheme



Studied Setup




PV: 68 m² Monocrystalline



ESS: 40kWh
(Renault Zoe)
Second-use battery

EV: Nissan Leaf
Charger: Type 2

EMR + Control + Strategy



Energy Management Strategy

EMS Main Objective: Maximum use of PV energy to charge EVs

Only ESS power is controllable

$$P_{ESS}^* = P_{ch} - P_{SPV} - P_{grid}$$

P_{ch} = Demanded power from EV charger


P_{SPV} = Power supplied by PV system

P_{ESS} = Power supplied by ESS

Check solar production

Check ESS SoC

Action on ESS



Maximum EV charging from PV system
ESS is not charged from grid



<https://cumin.univ-lille.fr/>




Solar modelling and results




PV system modelling

- Methodology



- Identification



Recording




Irr. & Temp.



Power

Recording




- Building 3D table model




Model validation

27th April 2025 chosen for validation


INPUT



OUTPUT



ERROR



2% error on energy production



Model validated



<https://cumin.univ-lille.fr/>



Case scenario results




PV-based charging station results for 2 days


Sunny Day- 29th April 2025



EV charging- 7hrs



Sufficient PV Energy




ESS usage- None


Cloudy Day- 20th April 2025



EV charging- 7hrs



Insufficient PV Energy



ESS usage- Maximum



<https://cumin.univ-lille.fr/>



ESS Aging Results



Second Life battery aging in a PV-based charging station


- Aging model

$$C_{\text{loss}_{t \rightarrow (t+dt)}} = d \left[(A + B\text{SoC}) e^{\frac{-Ea}{k_B T_{\text{Bat}}}} t^z + k_{\text{FEC}} \text{FEC}^\alpha \right]$$

→ $\text{SoH} = 100 - C_{\text{loss}_{0 \rightarrow t}}$

Parameter Identification for Zoe [Ndiaye 2024]

- Simulation results (second life)



→ 13% SoH degradation in 10 years

Conclusion, and perspective

- Conclusion
 - 13% SoH degradation in 10 years
 - 2% error on SPV power prediction
- Perspective
 - Simplified model of PV-based charging station
 - EMR of the system
 - Validated model of SPV
 - Model battery aging in second life

Acknowledgement

This work is supported by the French Government, managed by the National Research Agency through 3rd PIA, integrated into France 2030, under Reference ANR-21-IDES0006, and by the Hauts-de-France Region under the framework of WILL and CUMIN Programs of the University of Lille.



This work is also achieved within the framework of the EE4.0 (Energie Electrique 4.0) project. EE4.0 is co-financed by European Union with the financial support of the European Regional Development Fund (ERDF), the French State and the French Region of Hauts-de-France.




Questions?

Contact info: **Bibaswan Bose**


Website: www.bibaswanbose.com

Email: bibaswanbose@gmail.com

Phone no.: +33-(0)758507575



<https://cumin.univ-lille.fr/>



Our university as an exciting living lab towards eco-cities through an innovative transdisciplinary framework !

